



SD-24

Thin Surface Mount LED Light

SD-24 LED

Benefits

- This surface mount LED warning light offers maximum performance with minimum size (3" x 1" x .4")
- Its small footprint allows it to be mounted to locations such as push bumpers, rear bumpers, license plate areas, and running boards while its slim design keeps a low profile look.
- Low current draw and long maintenance-free service life

Design Features

- 24 (1) watt high-intensity LEDs
- 16 flash patterns
- Red, blue, amber, and white LEDs available
- Synchronizable with the Volt, Wildcat, Zenith and other SD24s
- In-line waterproof driver module
- UV stabilized polycarbonate lens
- Pre-wired 9' cable
- Colorless when not illuminated

Options

- Chrome bezel (SD24CH)
- L bracket (SD24LBRKT)
- Multi-angle bracket (SD24ZBRKT)

Specifications

- Dimensions without grommet: 3.3" W x 1.1" H x 0.4" D (83.8 mm x 27.9 mm x 10.2 mm)
- Dimensions with grommet: 3.67" W x 1.45" H x 0.46" D (93 mm x 37 mm x 12 mm)
- 12/24 Volt
- 0.75 Amps
- Meets SAE J595, R10 when properly configured
- Class I (amber, blue, white & red) when properly configured
- Meets CA T13 (amber, blue & red) when properly configured CE
- Temperature range: -22°F to 122°F (-30°C to +50°C)
- 5-Year warranty

SD24LBRKT	SD24ZBRKT	SD24BEZ	SD24CH
		 Included	



ELEKTROAROLA