

M37 R65

3LED LIGHTHEAD



FEATURES

- Multi-Voltage Input 12~24VDC
- Built-in 16 Selectable Flash Patterns
- LEDs rated to 100,000 hours of operation.
- Non-volatile memory recalls last flash pattern used at power up.
- Multiple units are synchronizable and can flash simultaneously or alternately.
- Reverse polarity protection.
- Weatherproof and vibration resistant design for external or internal use.

SPECIFICATIONS

Meets: ECE R65 XA1

Bulb: 1W LED x 3pcs

Warning Patterns: 16 Flash Patterns

Operating Voltage: 12~24VDC

Avg. Current: 0.26A @12.8VDC / 0.14A @24VDC
(varies with flash pattern)

Avg. Power: 3.3 Watts (varies with flash pattern)

Max. Current: 0.52A @12.8VDC / 0.27A @24VDC

Max. Power: 6.6 Watts

Wires: Red-Vcc: 20cm (20AWG)

Black-GND: 20cm (20AWG)

Yellow-Flash Patterns & Sync: 20cm (20AWG)

White-Phase: 20cm (20AWG)

Fuse Recommend: 3A



Multi-Unit Synchronization: Over 15

Storage Temperature: -40°C to +80°C

Operating Temperature: -30°C to +65°C

Available in: AMBER

DIMENSIONS



PART NO.

- M37-2B03A-00 (AMBER, R65)

FLASH PATTERN

FP#	Flash Patterns		
1	Single (2Hz)	9	Double
2	Double (2Hz)	10	Triple
3	Triple (2Hz)	11	Quad
4	Quad (2Hz)	12	Quint
5	Random	13	Ultra
6	Steady	14	Single-Quad
7	Single	15	Single H/L
8	Mega	16	Singe-Triple-Quint

*2Hz Flash Patterns meets ECE R65 Flash rate requirements.



JULUEN ENTERPRISE CO.,LTD.

8F-1, No.502, Da An Rd., Shulin District, Xinbei City, Taiwan, 23849

TEL: +866-2-86873177 FAX: +866-2-86873166